

## Plastering machine type BAPRO one 230V STRONG MAX (230 Volt)

### standard equipment:

- stator and rotor type BAPRO SILA MAX 230V
- main gearmotor NORD 5,5 kW 286 rpm special edition BAP01
- tilt sensor of main engine (safety)
- infeed wheel gearmotor 0,55 kW 22 rpm special edition BAP02
- compressor oil-free diaphragm-piston HANDY K2 1,09 kW 230 Volts capacity 250 l/min
- compressor pressure switch
- material hose 25 mm 40 BAR, 15 meter, cpl. with hydraulically fitted couplings male and female rotating cpl.
- rubber air hose 1/2" 20 BAR, 16 meter included geka-coupling cpl.
- water hose 1/2", 5 meter with spraying nozzle
- cleaning tool and cleaning shaft for cleaning mixing chamber
- water/air fittings with valve to regulation of water 150 - 1500 l/h
- water pump type 50M
- mixing shaft
- long spraying gun 100 cm with round file to spray gun
- 4 rubber, rotatable wheels, including 2 with brake
- power cable 230V 3x4 mm<sup>2</sup>, 25 meter cpl.
- water hose 3/4" 20 BAR included geka-coupling 25 meter cpl.
- adapter filing material
- control system the machine between pump or mixing-pump

