

PLASTERING
MACHINE
type
BAPRO one
400 Volt





If you planning to grow your business on the basis of service for finishing work, as machine plaster gypsum, cement and lime or smooth floor our plastering machine will be the best solution. Plastering machine type **BAPRO one** 400V is the best mixing pump and sprayer for dry premixed materials. Our machine characterized by unique in design, high performance work, simple operation, easy to transportation, optimal dimensions outer. Such attributes are the unique characteristic of the BAPRO brand.



With this in mind created specifically for you highly efficient plastering unit **BAPRO** one. Now, you can comfortable perform your work at a prominent growth in labor productivity. Applied design solutions and the latest technology will affect the operating cycle and at the same time ensure a long trouble-free operation of your machine. Operation of the machine is very easy! Just purchase premixed material, then automatically followed the mixing material with water. Ready-mixed mortar is pumped by a high-performance screw pump (stator and rotor), by infeed hose to spray gun. Mortar is sprayed onto the substrate to yield a high rate of job growth while convenience. Construction of the machine allows it to move smoothly because of the 4 wheels rotated around its axis. Ease of transporting the stairs provide three parts of construction and strong transport handles. High quality and aesthetic of equipment will provide a easy handling the spraying operation. Do not delay in making a decision until tomorrow! Today, make sure that your company could grow quickly!

JAKOŚĆ

**QUALITY** 

गणु वत्ता

**KVALITA** 

ج ودة

Якасць

質量

Calidad

Qualität

Qualità

Качество





#### ADVANIAGES

- high-quality components
- ease of use and simple design
- high performance
- 5 year warranty
- wide range of applications
- operational reliability
- long distance of mortar conveying
- easy and safety transport
- low height of the hopper
- extensive hopper 130 liters
- compressor oil-free HANDY K2
- reinforced geared motors NORD
- the opportunity to work with such devices Pneumatic feeder mortar BAPRO 140T

Why BAPRO one 400 Volt?



# For us always count details!

Water block made of stainless steel. Dual water filtration system through the use of filters, cleaning protects the components. No damage to the fittings and switches since they are protected.

Electrical control box: dust protection and excellent ease of main- tenance. The best industrial automation system includes LEDs, enhanced aesthetics contactors and provides trouble-free control of the whole machine (high standard of work)

special gear motors NORD include mixed and pump gearmotor 5,5 kW and material feeder gearmotor 0,55 kW contains a special execution. Water pump type 50M ensures the continuity of work to stabilize the water pressure to provide the best consistency of the mortar.

the technology named "STRONG MAX" it allows you to do more work. BAPRO offer double system work between the mixing -pump or only pump so you can take advantage of even more potential plastering machine. With our system you can decide yourself whether you want to work on dry ready mortar how gypsum or lime-cement or assume we developed adapter and you are using the liquid materials such as facade plaster, glue.













H I g n performance
compressor
type HANDY
K2 gives
optimum spray
material. Is
maintenancefree and does
not contain oil
and include
pressure
switch.

Maximum stability due to the robust frame structure. Three Elemental reinforced structure gives great freedom of maneuver in the plumb or level and easy to transport. We offer system of four wheels rotatable about 360 degrees to facilitate the movement



Very good equipment and high quality (aesthetics) provides safety and convenience continuous work. Long spray gun 100cm with special rotary coupling. Material hose and air hose with special rubber.

#### **Technical data**

- Pumping : variable from 4 to 8 liter per minute
- Distance delivery : to 50 meter
- Power supply: 400 Volts / 50 Hz
- Drives: 2 three-phase motors 400V/50 Hz
- Gearmotor 5,5 kW 416 rpm
- Gearmotor 0,55 kW 29 rpm
- Compressor 900 W efficiency 250 I/min
- Dimensions L/W/H:1250/720/1530 mm
- Filing height: 90cm
- Total weight 260 kg

### RECOMMENDED

#### Gypsum plasters

Gypsum liment plaster

#### Cement - lime plaster

Lining plasters (renderings)

#### Light plasters

Restoration plaster / renovationg

#### **Decorative plasters**

Anhydrite floor screeds

**Bonding mortar** 

## **CONTACT**

- address: PL 45-920 Opole , Brzoskwiniowa 18 POLAND
- telephone: +48 77 45 66 447
- telephone: +48 606 91 40 40
- e-mail: info@bapro.com.pl
- website: www.bapro.com.pl

